

Current Transformer Models 606 & 608 Split Core

Window Sizes 2.75" x 2.70", 2.60"x 6.25"



APPLICATION:

For energy management systems and instrumentation.

FREQUENCY:

50-400 Hz.

INSULATION LEVEL:

0.6 kV, BIL 10 kV full wave.

CONTINUOUS THERMAL CURRENT RATING FACTOR:

Model 606:

1.33 at 30°C. amb., 1.00 at 55°C. amb.

Models 608-501 thru 608-202:

1.33 at 30°C. amb., 1.0 at 55°C. amb.

Models 608-252 thru 608-322:

1.0 at 30°C. amb., 0.7 at 55°C. amb.

Secondary Cable: Two No. 16 AWG 6 feet long,

Approximate Weight:

Model 606.....4.5 lbs.

Model 608.....7.5 lbs.

REGULATORY AGENCY APPROVALS



Model 606

Manufactured to meet the requirements of ANSI/IEEE C57.13.
Transformers comply with IEC 61689

CATALOG NUMBER	CURRENT RATIO	BURDEN VA	ACCURACY AT 60 HZ
606-201	200:5	2.5	2 %
606-251	250:5	3	1 %
606-301	300:5	3.5	1 %
606-351	350:5	4	1 %
606-401	400:5	5	1 %
606-501	500:5	6	1 %
606-601	600:5	8	1 %
606-751	750:5	10	1 %
606-801	800:5	12	1 %
606-102	1000:5	15	1 %
606-122	1200:5	20	1 %

REGULATORY AGENCY APPROVALS



Model 608

Manufactured to meet the requirements of ANSI/IEEE C57.13.
Transformers comply with IEC 61689

CATALOG NUMBER	CURRENT RATIO	BURDEN VA	ACCURACY AT 60 HZ
608-501	500:5	6	1 %
608-601	600:5	8	1 %
608-801	800:5	12	1 %
608-102	1000:5	13	1 %
608-122	1200:5	16	1 %
608-152	1500:5	25	1 %
608-162	1600:5	27	1 %
606-202	2000:5	33	1 %
608-252	2500:5	42	1 %
608-302	3000:5	50	1 %
608-322	3200:5	54	1 %

Model 608 & 608 Split Core

These transformers are designed for assembly to an existing electrical installation without the need for dismantling the primary bus or cables.

Caution:

Proper safety precautions must be followed during installation by a trained electrician. Never install while bus is energized.

The current transformer must have its secondary terminals short circuited or the burden connected, before energizing the primary circuit.

