

**Current Transformer
Model 137**
Window Diameter 5.50"

REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1.



APPLICATION:

Relaying and metering.

FREQUENCY:

50-400 Hz.

INSULATION LEVEL:

600 Volts, 10 kV BIL full wave.

Terminals are brass screws No. 10-32 with one flatwasher and lockwasher.

Order mounting bracket kit 0221B01528 separately.

Multi-ratios available on request.

Approximate weight 50 lbs.

CATALOG NUMBER	CURRENT RATIO	RELAY CLASS	ANSI METERING CLASS AT 60HZ					SECONDARY WINDING RESISTANCE (OHMS @ 75°C)	CONTINUOUS THERMAL RATING FACTOR	
			BO.1	BO.2	BO.5	BO.9	B1.8		@ 30°C	@ 55°C
137-500	50:5	C10	2.4	4.8	—	—	—	0.019	2.0	2.0
137-750	75:5	C20	1.2	2.4	4.8	—	—	0.029	2.0	2.0
137-101	100:5	C20	1.2	1.2	2.4	4.8	—	0.039	2.0	2.0
137-151	150:5 *	C20	0.6	0.6	1.2	2.4	4.8	0.058	2.0	2.0
137-201	200:5 *	C50	0.3	0.6	1.2	1.2	2.4	0.078	2.0	2.0
137-251	250:5 *	C50	0.3	0.3	0.6	1.2	1.2	0.097	2.0	2.0
137-301	300:5 *	C100	0.3	0.3	0.6	0.6	1.2	0.116	2.0	2.0
137-401	400:5 *	C100	0.3	0.3	0.3	0.3	0.6	0.155	2.0	2.0
137-501	500:5 *	C100	0.3	0.3	0.3	0.3	0.6	0.194	2.0	2.0
137-601	600:5 *	C200	0.3	0.3	0.3	0.3	0.3	0.233	2.0	2.0
137-751	750:5 *	C200	0.3	0.3	0.3	0.3	0.3	0.291	2.0	2.0
137-801	800:5 *	C200	0.3	0.3	0.3	0.3	0.3	0.390	2.0	2.0
137-102	1000:5 *	C200	0.3	0.3	0.3	0.3	0.3	0.488	2.0	1.5
137-122	1200:5 *	C400	0.3	0.3	0.3	0.3	0.3	0.585	2.0	1.5
137-152	1500:5 *	C400	0.3	0.3	0.3	0.3	0.3	0.678	1.5	1.33
137-162	1600:5 *	C400	0.3	0.3	0.3	0.3	0.3	0.723	1.5	1.33
137-202	2000:5 *	C400	0.3	0.3	0.3	0.3	0.3	0.903	1.5	1.0
137-252	2500:5 *	C400	0.3	0.3	0.3	0.3	0.3	1.129	1.5	1.0
137-302	3000:5 *	C400	0.3	0.3	0.3	0.3	0.3	1.279	1.33	1.0
137-352	3500:5 *	C400	0.3	0.3	0.3	0.3	0.3	1.492	1.0	0.8
137-402	4000:5 *	C400	0.3	0.3	0.3	0.3	0.3	2.136	1.0	0.8
137-502	5000:5 *	C400	0.3	0.3	0.3	0.3	0.3	4.199	0.6	0.3

Model 137

