

MODEL 308MR

Current Transformer with Multi-Ratio

Window Diameter 5.75"



REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C57.13. Classified by U.L. in accordance with IEC 44-1

Application

Relaying.

Frequency

50-400 Hz.

Insulation Level

600 Volt, 10 kV BIL full wave.

Terminals are brass screws No. 10-32 with one flatwasher and lockwasher.


The transformer winding is arranged so that the turns are fully distributed between all taps.

Order mounting bracket kit 0221B01527 separately.


Approximate weight 34 lbs.

Model 308MR

CATALOG NUMBER	RELAY CLASS	CONTINUOUS THERMAL RATING FACTOR	
		@30 °C	@ 55 °C
308-601MR	C100	2.0	2.0
308-122MR	C200	2.0	1.5
308-202MR	C400	1.5	1.0
308-302MR	C400	1.33	1.0
308-402MR	C400	1.0	0.8




Model 308-601MR




461 Boston Street, Unit E6, Topsfield, MA 01983
Toll Free (800) 644-9773 · Phone (978) 887-2020
meters@spectrumind.com


Model 308MR




Model 308-122MR



Model 308-402MR



Model 308-202MR



Model 308-302MR

