

MODEL 3P85

Current Transformer

Window Diameter 2.08"



REGULATORY AGENCY APPROVALS
 E93779  LR89403
Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1

Application

3 phase relay, metering and motor overload protection.

Frequency

50-400 Hz.

Insulation Level

600 Volts, 10 kV BIL full wave.

Terminals are brass studs No. 8-32 with one flatwasher, lockwasher and regular nut.

Flexible leads U. L. 1015, 105 °C., CSA approved, No. 16 AWG , 24" long are available.

Approximate weight 4 lbs.

Model 3P85

CATALOG NUMBER	CURRENT RATIO	V.A. ±1% CLASS	ANSI METERING CLASS AT 60 Hz					SECONDARY WINDING RESISTANCE (Ω@ 75°C)
			B0.1	B0.2	B0.5	B0.9	B1.8	
3P85-501	500:5	5	0.6	1.2	—	—	—	0.064
3P85-601	600:5	10	0.6	0.6	1.2	—	—	0.077
3P85-751	750:5	10	0.6	0.6	1.2	—	—	0.096
3P85-801	800:5	10	0.6	0.6	1.2	—	—	0.103
3P85-102	1000:5	10	0.3	0.6	0.6	—	—	0.129
3P85-122	1200:5	10	0.3	0.6	0.6	—	—	0.154
3P85-152	1500:5	10	0.3	0.6	0.6	—	—	0.243

Note: Holes at the top of the transformer case can be used for attaching auxiliary device mounting plate (not supplied).
If the application requires transformer mounted relays, etc. then transformer can be ordered with secondary leads configured in various ways (consult factory).
Originally designed for use with molded case circuit breakers and motor starters with 2.75" bus center lines.



461 Boston Street, Unit E6, Topsfield, MA 01983
Toll Free (800) 644-9773 · Phone (978) 887-2020
meters@spectrumind.com

Model 3P85

