

MODEL 785

Current Transformer

Window Diameter 6.50"



REGULATORY AGENCY APPROVALS



E93779



LR89403

Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1

Application

Relaying and metering.

Frequency

50-400 Hz.

Insulation Level

0.6 kV, BIL 10 kV full wave.

Continuous Thermal Current Rating Factor

50:5-1,200:5 & 2,000:5

2.0 at 30 °C. amb., 1.5 at 55 °C.

1,500:5,1,600:5 & ,2500:5

1.5 at 30 °C. amb., 1.33 at 55 °C. amb.

3,000:5-4,000:5

1.33 at 30 °C. amb., 1.0 at 55 °C. amb.

Secondary terminals are brass screws No. 10-32 with one flatwasher, lockwasher, accessible from either side. Approximate weight 58 lbs.

Excitation data available upon request.



461 Boston Street, Unit E6, Topsfield, MA 01983
Toll Free (800) 644-9773 · Phone (978) 887-2020
meters@spectrumind.com

Model 785

CATALOG NUMBER	CURRENT RATIO	RELAY CLASS	ANSI METERING CLASS AT 60 Hz				
			B0.1	B0.2	B0.5	B0.9	B1.8
785-500	50:5	C10	2.4	4.8	-	-	-
785-750	75:5	C20	1.2	1.2	4.8	-	-
785-101	100:5*	C20	0.6	1.2	2.4	-	-
785-151	150:5*	C50	0.6	0.6	1.2	2.4	-
785-201	200:5*	C50	0.3	0.3	0.6	1.2	2.4
785-251	250:5*	C50	0.3	0.3	0.6	1.2	2.4
785-301	300:5*	C100	0.3	0.3	0.3	0.6	1.2
785-401	400:5*	C100	0.3	0.3	0.3	0.6	1.2
785-501	500:5*	C100	0.3	0.3	0.3	0.3	0.6
785-601	600:5*	C200	0.3	0.3	0.3	0.3	0.6
785-751	750:5*	C200	0.3	0.3	0.3	0.3	0.3
785-801	800:5*	C200	0.3	0.3	0.3	0.3	0.3
785-102	1,000:5*	C200	0.3	0.3	0.3	0.3	0.3
785-122	1,200:5*	C400	0.3	0.3	0.3	0.3	0.3
785-152	1,500:5*	C400	0.3	0.3	0.3	0.3	0.3
785-162	1,600:5*	C400	0.3	0.3	0.3	0.3	0.3
785-202	2,000:5*	C400	0.3	0.3	0.3	0.3	0.3
785-252	2,500:5*	C400	0.3	0.3	0.3	0.3	0.3
785-302	3,000:5*	C400	0.3	0.3	0.3	0.3	0.3
785-402	4,000:5*	C400	0.3	0.3	0.3	0.3	0.3

Approved for revenue metering by Industry Canada No. AE-0657(*)



461 Boston Street, Unit E6, Topsfield, MA 01983
Toll Free (800) 644-9773 · Phone (978) 887-2020
meters@spectrumind.com

Model 785

