

MODELS CPTS3-60-15 & CPTS5-95-15

Medium Voltage Control Power Transformers



Application

To provide control power in medium voltage switchgear.

Frequency

60 Hz.

Insulation Level

CPTS3: 5 kV, 60 kV BIL full wave.

CPTS5: 15 kV, 95 kV BIL full wave.

Thermal Rating

15 kVA at 30°C ambient.

12.9 kVA at 55°C ambient.

Specifications

Primary terminals are brass screws 1/4-20 with one flatwasher and starwasher.

Secondary terminals are 1/2-13 brass studs with one flatwasher, lockwasher and two nuts, plus series/parallel links.

Supplied with $1 \pm 7 \frac{1}{2}\%$ or $2 \pm 2 \frac{1}{2}\%$ taps above and below nominal voltage on the primary winding.

Windings are encapsulated in epoxy resin.

Mounting base is steel.

Assembly is varnish coated.

Available as unfused only.

Self cooled.

For indoor use.

Approximate weight 290 lbs.

Model CPTS3-60-15 & CPTS5-95-15

**CATALOG NUMBER	PRIMARY VOLTAGE	RATIO	SECONDARY VOLTAGE	*FUSE RATING
CPTS3-60-15-242**	2,400 V	20:1	120/240 V	15E
CPTS3-60-15-4161**	4,160 V	34.7:1	120/240 V	10E
CPTS3-60-15-482**	4,800 V	40:1	120/240 V	10E
CPTS5-95-15-722**	7,200 V	60:1	120/240 V	7E
CPTS5-95-15-842**	8,400 V	70:1	120/240 V	7E
CPTS5-95-15-123**	12,000 V	100:1	120/240 V	5E
CPTS5-95-15-1242**	12,470 V	104:1	120/240 V	5E
CPTS5-95-15-1322**	13,200 V	110:1	120/240 V	5E
CPTS5-95-15-1382**	13,800 V	115:1	120/240 V	5E
CPTS5-95-15-1442**	14,400 V	120:1	120/240 V	5E

*Note all fuse rating are based on NEC transformer overcurrent protection recommendations. Specific applications may require other other ratings.

**For $1 \pm 7 \frac{1}{2}\%$ taps use suffix "A" after Catalog No.

**For $2 \pm 2 \frac{1}{2}\%$ taps use suffix "B" after Catalog No.



461 Boston Street, Unit E6, Topsfield, MA 01983

Toll Free (800) 644-9773 · Phone (978) 887-2020

meters@spectrumind.com

Models CPTS3-60-15 & CPTS5-95-15

Connection Diagrams

